

Flat collar  
**Tyvek®**



**EISEDICHT®**  
EASY. SAFE. SEAL.

## Technical Data Sheet

### Application fields:

Self-adhesive collar for sealing openings through the airtight level, e.g. for vapour barriers, sarking membranes.

### Adhesive sleeve

<b>Material:</b>	HDPE carrier film (Tyvek®) / polyacrylate adhesive glue
<b>Colour:</b>	white
<b>Thickness:</b>	approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm adhesive glue
<b>Adhesive force:</b>	> 25N/25mm
<b>Tensile strength:</b>	> 50N/25mm
<b>Temperature resistance:</b>	-30 °C bis +100 °C
<b>UV resistance:</b>	very good

### Flexible sealing membran

<b>Material:</b>	EPDM
<b>Colour:</b>	black
<b>Elongation at tear:</b>	≥ 300 % (EN 12311-2)
<b>Tensile strength:</b>	≥ 7 MPa (EN 12311-2)
<b>Thickness:</b>	1 mm ± 20%
<b>Fire protection class:</b>	E (EN 13501-1)

**Storage:** cool and dry

**Processing temperature:** +5 °C to +40 °C

**Processing notes:** The area must be dry, stable and free of dust and release agent. Folds, kinks and tensile stresses must be prevented.

The information in our data sheet is provided to the best of our knowledge, from the practical results and conducted tests. Previous data is therefore invalid. Check yourself whether the product is suitable for your purposes. Any potential liability on our part is restricted to the value of our product as such. We cannot assume any liability for indirect damages, in particular for the application or lack of usefulness of the product. Nobody is entitled to provide recommendations or assurances on our behalf, which extend beyond the content of our information sheets. We reserve the right to make changes to or further develop our products.