



Technical Data Sheet

Application fields:

Self-adhesive collar with weatherproof surface including universal device holder for sealing and fastening rooftop mounts on sloping roofs.

Adhesive sleeve

Material:

creped aluminium fully coated with butyl and reinforcement inlay made from polyester composite material

Colour:

brick red, black, anthracite, zinc grey, dark brown

Thickness:

approx. 1.2 mm

Temperature resistance:

-20 °C to +80 °C

UV resistance:

ensured by metal surface

Flexible sealing grommet

Material:

EPDM

Colour:

black

Hardness:

60 ± 5 Shore A (DIN ISO 48)

Density:

1.15 g / cm³ (DIN ISO 1183-1)

Tensile strength:

11.6 MPa (DIN ISO 37)

Temperature resistance:

-30 °C to +100 °C

UV resistance:

very good

Universal device holder

Material:

cast aluminium

Colour:

silver

Diameter:

M 8 thread

Base area:

206 x 116 mm

Compressive force:

1.50 kN

Tensile force:

1.49 kN

Transverse (vertical):

1.00 kN

Storage:

cool and dry

Processing temperature:

+5 °C to +40 °C

Roof pitch:

> 10°

Bitumen compatibility:

yes

Unleaded:

yes

Processing notes:

The area must be dry, stable and free of dust and release agent. Folds and kinks must be prevented.