



Technical Data Sheet

Application fields:

Self-adhesive collar for sealing pipe openings through e.g. underlays and sarking membranes. With integrated HT-Safe® moulded part for windproof and airtight pipe routing through the roof level, e.g. ventilation tiles.

Adhesive sleeve

Material:

HDPE carrier film (Tyvek®) / polyacrylate adhesive glue

Colour:

white

Thickness:

approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm adhesive glue

Adhesive force:

> 25N/25mm

Tensile strength:

> 50N/25mm

Temperature resistance:

-30 °C to +100 °C

UV resistance:

very good

Flexible sealing grommet

Material:

EPDM

Colour:

black

Hardness:

60 ± 5 Shore A (DIN ISO 48)

Density:

1.15 g / cm³ (DIN ISO 1183-1)

Tensile strength:

11.6 MPa (DIN ISO 37)

Temperature resistance:

-30 °C to +100 °C

UV resistance:

very good

Integrated HT-Safe® moulded part

Material:

polypropylene (PP)

Colour:

grey

Storage:

cool and dry

Processing temperature:

+5 °C to +40 °C

Halogen-free:

yes

Processing notes:

The area must be dry, stable and free of dust and release agent.
Folds and kinks must be prevented.