



## Technical Data Sheet

### Application fields:

Self-adhesive collar for sealing heat-resistant openings through the airtight level, e.g. for vapour barriers, sarking membranes. Heat-resistant up to 250°C.

### Adhesive sleeve

**Material:**

HDPE carrier film (Tyvek®) / polyacrylate adhesive glue

**Colour:**

white

**Thickness:**

approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm adhesive glue

**Adhesive force:**

> 25N/25mm

**Tensile strength:**

> 50N/25mm

**Temperature resistance:**

-30 °C to +100 °C

**UV resistance:**

very good

### Flexible sealing grommet

**Material:**

heat-stabilised silicone

**Colour:**

red

**Hardness:**

60 ± 5 Shore A (DIN 53505)

**Density:**

1.17 g / cm<sup>3</sup> (DIN EN ISO 1183-1A)

**Tear strength:**

≥ 8 MPa (DIN 53504-S2)

**Temperature resistance:**

-50 °C to +200 °C (short-term 250 °C)

**UV resistance:**

very good

**Storage:**

cool and dry

**Processing temperature:**

+5 °C to +40 °C

**Halogen-free:**

yes

**Processing notes:**

The area must be dry, stable and free of dust and release agent.

Folds and kinks must be prevented.