

Airtight Sealing Collars

Tyvek®



EISEDICHT[®]
EASY. SAFE. SEAL.

Technical Data Sheet

Application fields:

Self-adhesive collar for sealing openings through the airtight level, e.g. for vapour barriers, sarking membranes.

Adhesive sleeve

Material:

HDPE carrier film (Tyvek®) / polyacrylate adhesive glue

Colour:

white

Thickness:

approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm adhesive glue

Adhesive force:

> 25N/25mm

Tensile strength:

> 50N/25mm

Temperature resistance:

-30 °C to +100 °C

UV resistance:

very good

Flexible sealing grommet

Material:

EPDM

Colour:

black

Hardness:

60 ± 5 Shore A (DIN ISO 48)

Density:

1.15 g / cm³ (DIN ISO 1183-1)

Tensile strength:

11.6 MPa (DIN ISO 37)

Temperature resistance:

-30 °C to +100 °C

UV resistance:

very good

Storage:

cool and dry

Processing temperature:

+5 °C to +40 °C

Halogen-free:

yes

Processing notes:

The area must be dry, stable and free of dust and release agent.

Folds and kinks must be prevented.

The information in our data sheet is provided to the best of our knowledge, from the practical results and conducted tests. Previous data is therefore invalid. Check yourself whether the product is suitable for your purposes. Any potential liability on our part is restricted to the value of our product as such. We cannot assume any liability for indirect damages, in particular for the application or lack of usefulness of the product. Nobody is entitled to provide recommendations or assurances on our behalf, which extend beyond the content of our information sheets. We reserve the right to make changes to or further develop our products.