



Technical Data Sheet

Areas of application:

Prefabricated self-adhesive internal and external corners for permanent and secure sealing against harmful gases, for corner situations on floor slabs (above or below), walls or ceilings.

Base material

Material:	butyl rubber / aluminium-plastic hybrid lamination
Colour:	brown / black
Thickness:	approx. 1 mm butyl adhesive / approx. 0.1 mm hybrid film
Solids content:	>99 % (DIN EN ISO 10563)
Butyl density:	approx. 1.5 g / cm ³ (DIN EN ISO 10563)
Temperature resistance:	-40 °C to +100 °C
UV resistance:	very good

Integrated Flex-Point

Material:	Highly flexible PE film with scrim / Reinarcylat pressure-sensitive adhesive
Base colour:	black
Thickness:	approx. 0.5mm
Temperature resistance:	-40 °C to +80 °C
UV resistance:	outdoor exposure time with UV exposure 12 months

Storage: cool and dry

Processing temperature: +5 °C to +30 °C
Bitumen compatibility: yes

Application instructions:

The surface must be dry, load-bearing, free of dust and release agents. Porous substrates such as concrete, plaster, etc. must be treated in advance with BUBI LF Adhesion Primer or Eisedicht Spray Primer. Avoid folds, creases and tensile stresses.