



## Technical Data Sheet

<b>Areas of application:</b>	Self-adhesive collar with high weather resistance, for inconspicuous sealing of penetrations through curtain-type, rear-ventilated facade membranes.
<b><u>Adhesive collar</u></b>	
<b>Material:</b>	UV-stable fleece composite / acrylic pressure-sensitive adhesive
<b>Colour:</b>	black
<b>Thickness:</b>	approx. 0.25 mm non-woven backing / approx. 0.15 mm pressure-sensitive adhesivem
<b>Tensile strength:</b>	250N/50mm
<b>Temperature resistance:</b>	-40 °C to +80 °C
<b>UV resistance:</b>	very good
<b><u>Flexible sealing grommet</u></b>	
<b>Material:</b>	EPDM
<b>Color:</b>	black
<b>Hardness:</b>	60 ± 5 Shore A (DIN ISO 7619-1)
<b>Density:</b>	1.15 g / cm <sup>3</sup> (DIN ISO 1183-1)
<b>Tensile strength:</b>	11.6 MPa (DIN ISO 37)
<b>Temperature resistance:</b>	-30 °C to +100 °C
<b>Storage:</b>	cool and dry
<b>Processing temperature:</b>	+5 °C to +30 °C
<b>Processing instructions:</b>	The surface must be dry, load-bearing and free of dust and release agents. Avoid folds and creases.