



Technical Data Sheet

Areas of application:

Self-adhesive sleeve for airtight and windproof sealing of penetrations in the attica area (roof drains) in the flat roof level. For substrates such as concrete, sand-lime brick, soft wood fibre boards, OSB boards, bituminous sheeting (not in the top layer).

Adhesive collar

Material:	aluminium-plastic composite film / butyl rubber
Colour:	brown / black
Thickness:	approx. 0.1 mm composite foil / approx. 1 mm butyl adhesive
Butyl density:	approx. 1.5 g / cm ³ (DIN EN ISO 10563)
Tensile strength:	11.6 MPa (DIN ISO 37)
Temperature resistance:	-40 °C to +100 °C
UV resistance:	very good

Flexible sealing grommet

Material:	EPDM
Colour:	black
Hardness:	60 ± 5 Shore A (DIN ISO 7619-1)
Density:	1.15 g / cm ³ (DIN ISO 1183-1)
Tensile strength:	11.6 MPa (DIN ISO 37)
Temperature resistance:	-30 °C to +100 °C
UV resistance:	very good

Storage: cool and dry

Working temperature:	+5 °C to +30 °C
Bitumen compatibility:	yes
Halogen-free:	yes

Application instructions:

The surface must be dry, load-bearing and free of dust and release agents. Porous substrates such as concrete, plaster, etc. must be treated in advance with BUBI LF Adhesion Primer or Eisedicht Spray Primer. In the case of bituminous membranes, the sanding and/or protective film must be removed, e.g. by heating. Avoid folds and creases.