



Technical Data Sheet

Areas of application:

Self-adhesive sleeve for a reliable sealing of up to six penetrations through the airtight layer. Suitable for substrates such as vapour retarders, vapour barriers, underlays or climate membranes.

Hard component

Material base: PP block copolymer type

Colour: Red

Density: 0.90 g/cm³ (DIN EN ISO 1183-1)

Tensile, E-modulus: 1100MPa (DIN EN ISO 527)

Izod notched impact: 11 kJ/m² (ISO 180/1A)

Soft component

Material basis: TPS-SEBS+PP (ISO 18064)

Colour: Grey

Density: 1.05 g/cm³ (DIN EN ISO 1183-1)

Hardness: 30 SHA (DIN 53 505)

Elongation at break: 11 kJ/m² (ISO 180/1A)

Tensile strength longitudinal: 3 N/mm² (DIN 53 504)

Adhesive collar

Material: HDPE carrier film (Tyvek®) / polyacrylate pressure sensitive adhesive

Colour: white

Thickness: approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm pressure sensitive adhesive

Adhesive strength: > 25N/25mm

Tensile strength: > 50N/25mm

Temperature resistance: -30 °C to +100 °C

UV resistance: very good

Storage: cool and dry

Processing temperature: +5 °C to +30 °C

Bitumen compatibility: yes

Halogen-free: yes

Processing instructions: The surface must be dry, load-bearing and free of dust and release agents. Avoid folds and creases.