



Technical Data Sheet

Application fields:

Self-adhesive collar with weatherproof surface including universal device holder for sealing and fastening rooftop mounts on sloping roofs.

Adhesive sleeve

Material:

creped aluminium fully coated with butyl and reinforcement inlay made from polyester composite material

Colour:

brick red, black, anthracite, zinc grey, dark brown

Thickness:

approx. 1.2 mm

Temperature resistance:

-20 °C to +80 °C

UV resistance:

ensured by metal surface

Flexible sealing grommet

Material:

EPDM

Colour:

black

Hardness:

60 ± 5 Shore A (DIN ISO 48)

Density:

1.15 g / cm³ (DIN ISO 1183-1)

Tensile strength:

11.6 MPa (DIN ISO 37)

Temperature resistance:

-30 °C to +100 °C

UV resistance:

very good

Universal device holder

Material:

cast aluminium

Colour:

silver

Diameter:

M 8 thread

Base area:

206 x 116 mm

Compressive force:

1.50 kN

Tensile force:

1.49 kN

Transverse (vertical):

1.00 kN

Storage:

cool and dry

Processing temperature:

+5 °C to +40 °C

Roof pitch:

> 10°

Bitumen compatibility:

yes

Lead-free:

yes

Processing notes:

The area must be dry, stable and free of dust and release agent. Folds and kinks must be prevented.

The information in our data sheet is provided to the best of our knowledge, from the practical results and conducted tests. Previous data is therefore invalid. Check yourself whether the product is suitable for your purposes. Any potential liability on our part is restricted to the value of our product as such. We cannot assume any liability for indirect damages, in particular for the application or lack of usefulness of the product. Nobody is entitled to provide recommendations or assurances on our behalf, which extend beyond the content of our information sheets. We reserve the right to make changes to or further develop our products.