



Technical Data Sheet

Areas of application:

Due to the enlarged adhesive surface, the DachDICHT Komfort folded penetration sleeves enable a convenient connection of penetrations to e.g. underlayment or sarking membranes, even underneath already positioned through-tiles. Suitable for roof pitches of <math><45^\circ</math>.

Adhesive collar

Material:	aluminium-plastic composite film / butyl rubber
Colour:	brown / black
Thickness:	approx. 0.1 mm composite foil / approx. 1 mm butyl adhesive
Butyl density:	approx. 1.5 g / cm ³ (DIN EN ISO 10563)
Temperature resistance:	-40 °C to +100 °C
Outdoor exposure:	6 months

Flexible sealing grommet

Material:	EPDM
Colour:	black
Hardness:	60 ± 5 Shore A (DIN ISO 48)
Density:	1.15 g / cm ³ (DIN ISO 1183-1)
Tensile strength:	11.6 MPa (DIN ISO 37)
Temperature resistance:	-30 °C to +100 °C
UV resistance:	very good

Storage: cool and dry

Processing temperature:	+5 °C to +30 °C
Bitumen compatibility:	yes
Halogen-free:	yes

Application instructions:

The surface must be dry, load-bearing and free of dust and release agents. Porous substrates such as concrete, plaster, etc. must be treated in advance with BUBI LF Adhesion Primer or Eisedicht Spray Primer. In case of bituminous membranes, the sanding and/or protective film must be removed, e.g. by heating. Avoid folds and creases.