



Technical Data Sheet

Areas of application:

Due to the enlarged adhesive surface, the DachDICHT Komfort folded penetration sleeves enable a convenient connection of penetrations to e.g. underlayment or sarking membranes, even underneath already positioned through-tiles. Suitable for roof pitches of <math><45^\circ</math>.

Adhesive collar

Material:	HDPE carrier film (Tyvek®) / polyacrylate adhesive
Colour:	white
Thickness:	approx. 0.2 mm Tyvek® carrier film / approx. 0.12 mm pressure-sensitive adhesive
Adhesive collar:	> 25N/25mm (DIN 4108-11)
Tensile strength:	> 50N/25mm (DIN 4108-11)
Temperature resistance:	-30 °C to +120 °C
Outdoor exposure:	6 months

Flexible sealing grommet

Material:	EPDM
Colour:	black
Hardness:	60 ± 5 Shore A (DIN ISO 48)
Density:	1.15 g / cm ³ (DIN ISO 1183-1)
Tensile strength:	11.6 MPa (DIN ISO 37)
Temperature resistance:	-30 °C to +100 °C
UV resistance:	very good

Storage: cool and dry

Processing temperature: +5 °C to +40 °C

Halogen-free: yes

Application instructions: The surface must be dry, load-bearing, free of dust and release agents. Avoid folds and creases.